



NOTES:

COUNCI

BΥ

APP.

DATE

BΥ

REVISION

- 1. JOINTS TO BE CONSTRUCTED AS REQUIRED BY STANDARD SPECS. FOR SEWER LINE.
- 2. IF IN STREET OR ALLEY USE CLASS "A" CONCRETE $\rm W/$ 5 POUNDS OF LAMP BLACK PER CUBIC YARD.
- 3. FOR APPURTENANCES LOCATED IN EASEMENT: FINISHED GRADE FROM EDGE OF CONCRETE SHALL SLOPE DOWN NO LESS THAN 6" AND NO MORE THAN 18", MEASURED FROM THE TOP OF CONCRETE SURFACE.

A=

- •18" ON ARTERIAL AND COMMERCIAL STREETS
- •12" ON COLLECTOR AND COMM STREETS
- •8" ON LOCAL AND RESIDENTIAL STREETS

SS = QUANTITY PAYMENT LIMITS FOR CITY CONTRACTS

STANDARD PLAN

DRAWN BY: GL DATE: 02/2016 CHECKED BY: BO SCALE: NONE APPROVED: Ott

PUBLIC WORKS DIRECTOR-ENGINEERING

TYPICAL METHOD FOR SETTING APPURTENANCES

NO. S-13

SHEET 1 OF 1