## **TABLE 16.11-2** OFFICE DISTRICTS GENERAL DEVELOPMENT STANDARDS(1) (2) Office **ORP Development Feature Required Building Setbacks** Street Side 25 feet 25 feet Interior 25 feet 25 feet Interior (adjacent to residential zoned properties) Twice Building Height Twice Building Height Interior (adjacent to a freeway) 25 feet minimum 25 feet minimum **Building Height** Maximum Building Height<sup>(3)</sup> 90 feet 150 feet Consistent with Section 16.44.150 **Accessory Structures** Landscaping 20 percent Minimum On-site Landscaping<sup>(4)</sup> 20 percent Minimum Parking Area Landscaping Based on Parking Lot Size<sup>(5)</sup> 5 - 24 spaces 5 percent 5 percent 25 - 49 spaces 7.5 percent 7.5 percent 50 spaces plus 10 percent 10 percent **Parking Requirements**

See Chapter 16.34, Off-Street Parking and Loading Standards

- (1) Portions of a site may be developed prior to development of the entire site, if it can be demonstrated that the portion does not compromise the overall comprehensive development of the site.
- Development standards may vary for mixed use projects and projects over ten acres in size when comprehensively planned in compliance with Chapter 16.64, Master Development Plans, or Chapter 16.66, Specific Plans.
- (3) For structures greater than fifty (50) feet in building height and within 500 feet of existing residential homes, a public hearing shall be required, and the review shall include an evaluation of view sheds to maintain views for residential homes and a shadow survey to avoid buildings casting shadows on residential homes.
- (4) See Chapter 16.28, Landscaping Standards and Water Efficient Landscaping.
- (5) Minimum required parking lot landscaping area is included in required minimum on-site landscaping area.

(Ord. 538, Exhibit A (part), 2018; Ord. 492 Exhibit 6, 2014)